# **PRODUCT SPECIFICATION**

Product name: Solar cell module

Model: M-30W

Product size: 600mm\*350mm

### 1. Scope

This product specification book standardizes the size, performance and test method of the product as the basis of technical confirmation.

### 2. General Specification

1. Application: The product can be used in solar modules, solar power generation systems, solar energy application products and other fields.

2. The standard test conditions :AM1.5, 1000W/m², 25°C

#### 3. Main Material

Specification	600mm*350mm
Battery cell specifications	Monocrystalline 157mm*30mm*36pcs
Material	Ultra white cloth grain tempered glas s, PET, EVA, photovoltaic welding tape
Encapsulation way	Glass laminate package
Frame	Anodized aluminum alloy frame

#### 4. Product Parameters:

Pm	30W
Vmp	18V
Imp	1.66A
Voc	21. 24V
Isc	1.85A
Maximum System Voltage	750V

## 5. Environmental conditions for use and storage:

- 1. Reserving environment:  $-20^{\circ}\text{C} 60^{\circ}\text{C}$ .
- 2. Outdoor environment with no shade under the sun.
- 3. Soldering temperature  $370\pm5$ °C, welding time should not exceed 3 seconds.

# 6. Points to note

- 1. Do not exceed the power range.
- 2. Avoid scratching the surface with hard objects during use.
- 3. Cannot bear bending force during transportation and assembly.
- 4. Do not contact with strong corrosive substances, if there is, should be cleaned immediately.
- 5. When connecting solar panels with electrical appliances, pay attention to whether the connection line is short-circuited, and whether the positive and negative poles are connected to reversing