

# Power Transistor (50V, 3A)

## 2SD1760 / 2SD1864


### ●Features

- 1) Low  $V_{CE(sat)}$ .  
 $V_{CE(sat)} = 0.5V$  (Typ.)  
 $(I_c/I_b = 2A / 0.2A)$
- 2) Complements the 2SB1184 / 2SB1243.

### ●Structure

Epitaxial planar type  
 NPN silicon transistor

### ●External dimensions (Units : mm)



### ●Absolute maximum ratings (Ta = 25°C)

Parameter	Symbol	Limits	Unit	
Collector-base voltage	$V_{CBO}$	60	V	
Collector-emitter voltage	$V_{CEO}$	50	V	
Emitter-base voltage	$V_{EBO}$	5	V	
Collector current	$I_c$	3	A (DC)	
		4.5	A (Pulse) *1	
Collector power dissipation	2SD1760 2SD1864	$P_c$	15	W (Tc = 25°C)*2
			1	W
Junction temperature	$T_j$	150	°C	
Storage temperature	$T_{stg}$	-55~+150	°C	

\*1 Single pulse,  $P_w = 100ms$

\*2 Printed circuit board, 1.7mm thick, collector copper plating 100mm<sup>2</sup> or larger.

Transistors

●Electrical characteristics (Ta = 25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Collector-base breakdown voltage	BV <sub>CB0</sub>	60	-	-	V	I <sub>c</sub> = 50μA
Collector-emitter breakdown voltage	BV <sub>CE0</sub>	50	-	-	V	I <sub>c</sub> = 1mA
Emitter-base breakdown voltage	BV <sub>EB0</sub>	5	-	-	V	I <sub>E</sub> = 50μA
Collector cutoff current	I <sub>CB0</sub>	-	-	1	μA	V <sub>CB</sub> = 40V
Emitter cutoff current	I <sub>EB0</sub>	-	-	1	μA	V <sub>EB</sub> = 4V
Collector-emitter saturation voltage	V <sub>CE(sat)</sub>	-	0.5	1	V	I <sub>c</sub> /I <sub>b</sub> = 2A/0.2A
DC current transfer ratio	h <sub>FE</sub>	82	-	390	-	V <sub>CE</sub> = 3V, I <sub>c</sub> = 0.5A
Transition frequency	f <sub>T</sub>	-	90	-	MHz	V <sub>CE</sub> = 5V, I <sub>E</sub> = -500mA, f = 30MHz
Output capacitance	C <sub>ob</sub>	-	40	-	pF	V <sub>CB</sub> = 10V, I <sub>E</sub> = 0A, f = 1MHz

\* Measured using pulse current.

●Packaging specifications and h<sub>FE</sub>

Type	h <sub>FE</sub>	Package	Taping	
		Code	TL	TV2
		Basic ordering unit (pieces)	2500	2500
2SD1760	PQR		○	-
2SD1864	PQR		-	○

h<sub>FE</sub> values are classified as follows:

Item	P	Q	R
h <sub>FE</sub>	82~180	120~270	180~390

●Electrical characteristic curves




Fig.1 Grounded emitter propagation characteristics




Fig.2 Grounded emitter output characteristics ( I )




Fig.3 Grounded-emitter output characteristics( II )




Fig.4 DC current gain vs. collector current( I )




Fig.5 DC current gain vs. collector current( II )




Fig.6 Collector-emitter saturation voltage vs. collector current

Transistors




Fig.7 Collector-emitter saturation voltage vs. collector current  
Base-emitter saturation voltage vs. collector current




Fig.8 Gain bandwidth product vs. emitter current




Fig.9 Collector output capacitance vs. collector-base voltage




Fig.10 Safe operating area (2SD1760)




Fig.11 Transient thermal resistance (2SD1760)




Fig.12 Safe operating area (2SD1864)




Fig.13 Transient thermal resistance (2SD1864)