



東莞市智旭電子有限公司
 JYH HSU (JEC) ELECTRONICS LTD.,

文件编号: P015
 版本: 0
 制定日期: 2020.08.20

承认书

SPECIFICATION FOR APPROVAL

客户名称

CUSTOMER

品名

PART NAME

capacitor

客户料号

Customer Part No:

承認規格

APPROVE ITEM

please refer to the list

供应商料号

Part Number

please refer to the list

日期

DATE

2024.9.3

客户承认

Customer approval

供应商承认

Supplier admit that



台湾:智旭电子有限公司
 JYH HSU(JEC) ELECTRONICSLTD
 台湾台中大里市仁路 222 巷 64 号
 TEL: 886-422752703
 FAX: 886-422752236
 E-mail: vinkyuan@gmail.com

广东: 智旭电子有限公司
 JYH HSU(JEC) ELECTRONICS LTD
 东莞市道窖镇蔡白村道厚路律冲桥头旁
 TEL: 0769-88313601 88313602
 FAX: 0769-88313603
 E-mail: vinkyuan@gmail.com

Product List

NO.	Model	Capacity (uf)	Voltage (V)	Tolerance (%)	Size D*L (mm)	operating temperature	P/N
1	3.5uF 450VAC	3.5	450	±5	30*57	-25°C~85°C	355J450V30*57
2	8uF 450VAC	8	450	±5	34*65	-25°C~85°C	805J450V34*65
3	25uF 450VAC	25	450	±5	40*70	-25°C~85°C	256J450V40*70
4	2.5uF 450VAC	2.5	450	±5	30*57	-25°C~85°C	255J450V30*57
5	12uF 450VAC	12	450	±5	40*70	-25°C~85°C	126J450V40*70
6	30uF 450VAC	30	450	±5	45*90	-25°C~85°C	306J450V45*90
7	45uF 450VAC	45	450	±5	45*95	-25°C~85°C	456J450V45*95
8	60uF 450VAC	60	450	±5	50*106	-25°C~85°C	606J450V50*106
9	14uF 450VAC	14	450	±5	40*70	-25°C~85°C	146J450V40*70
10	6uF 450VAC	6	450	±5	34*60	-25°C~85°C	605J450V34*60
11	16uF 450VAC	16	450	±5	40*70	-25°C~85°C	166J450V40*70
12	10uF 450VAC	10	450	±5	34*60	-25°C~85°C	106J450V34*60
13	4uF 450VAC	4	450	±5	30*57	-25°C~85°C	405J450V30*57

CBB60 Capacitor Specifications

This capacitor uses metallized film with thickened edges as electrodes and dielectrics. The components inside are wrapped with flame-retardant epoxy resin. The appearance of this product is cylindrical, with ABS or PBT plastic shell. It has good stability and moisture resistance.

Technical Specifications

·Implementation standard: GB/T3667-2005

Use requirements:

- Altitude: <2000m
 - Residual voltage when put into use: not more than 10% of the rated voltage
 - Maximum allowable voltage: not more than 1.1 times the rated voltage
 - Maximum allowable current: not more than 1.3 times the rated current
- Specifications and dimensions (mm)

Product model: CBB60

appearance: cylindrical

Dielectric material: metallized film

Adjustment method: fixed

Lead type: 4 plug-in

Withstand voltage: 450 (V)

